

ALPHA

Performance Packages



GT-R UNDER BODY FUEL LINE BRACKETS
INSTALLATION INSTRUCTIONS

The goal of Alpha Performance is to provide the highest quality, best performing products available. By utilizing research and development, and rigorous testing programs Alpha Performance will never compromise the quality or performance of our products. In addition, Alpha Performance will only provide the finest customer service offering only parts and advice that are in the best interests of the customer. Alpha Performance was built on a foundation of integrity. This is who we are; this is what you can count on.

A vehicle modified by the use of performance parts may not meet the legal requirements for use on public roads. Federal and state laws prohibit the removal, modification, or rendering inoperative of any part or element of design affecting emissions or safety on motor vehicles used for transporting persons or property on public streets or highways. Use or installation of performance parts may adversely affect the drivability and reliability of your vehicle, and may also affect or eliminate your insurance coverage, factory warranty, and/or new OEM part warranty. Performance parts are sold as-is without any warranty of any type. There is no warranty stated or implied due to the stresses placed on your vehicle by performance parts and our inability to monitor their use, tuning, or modification.

These instructions are provided as a guide only as there are many variables that cannot be accounted for concerning your particular vehicle, including but not limited to model year differences, model differences, the presence of non-OEM parts, and modifications that may already be or were previously installed. A basic knowledge of automotive parts and systems is helpful but a better understanding of the parts and systems on your particular vehicle may be required.

If you have any questions or issues at any time during the installation of your Alpha Performance product(s) please call us for technical assistance. The Alpha Performance tech line can be reached during business hours at 847-709-0530 for Alpha Performance products only.

Under Body Fuel Line Bracket Installation

1. Remove the factory fuel and brake line retaining clips from the vehicle. Take care when removing the plastic clips from the studs on the body of the car.
2. Test fit the fuel lines you will be installing in the billet under car brackets. Before pulling the backing off the adhesive side of the supplied rubber stripping, test fit the fuel line into the bracket. You are looking for a snug fitment in the saddle and against the body of the car holding the fuel line in place without pinching it.
3. Fit and cut the rubber stripping to the size required for each saddle to secure the fuel line in the saddle of the bracket.



Note: The Size of the saddles are noted below

- 21mm for the large saddle accepting a hose OD up to a 21.5mm
- 17mm for the small saddle accepting a hose OD up to 17.5mm

4. Install the brackets onto the studs where the factory plastic clips were located. Use the supplied collar nuts.

Note: Do not over tighten the nuts on the studs. Doing so will run the risk of breaking the studs off the body of the car.

